

Jednostka wentylacyjna z odzyskiem ciepła		Jednofazowe	
		1.76 kW	1.76 kW
Left side connection		—	PAW-A2W-VENTA-L
Right side connection		PAW-A2W-VENTA-R	—
Nominal air flow rate at 50Pa	m³/h	204	204
Maximum air flow rate at 100Pa	m³/h	292	292
SPF at 204m³/h		1,24	1,24
Heat exchanger rotor drive type		Variable speed	Variable speed
Exchanger type		Rotating	Rotating
Heat recovery efficiency	%	84	84
Power supply (Voltage)	V	230	230
Power supply (Phase)		Single phase	Single phase
Power supply (Frequency)	Hz	50	50
Power consumption	W	176	176
Energy Class, basic unit		A	A
Energy Class, unit with local control on demand		A	A
Sound pressure	dB(A)	40	40
Dimension (Height)	mm	450	450
Dimension (Width)	mm	598	598
Dimension (Depth)	mm	500	500
Net weight	kg	46	46
Duct connections		DN125	DN125
Filter class, supply air		F7/ePM1 60%	F7/ePM1 60%
Filter class, extract air		M5/ePM10 50%	M5/ePM10 50%
Minimum outdoor temperature	°C	-20	-20

* Efektywność odzysku ciepła zgodnie z normą EN 13141-7.

** Jednostka wentylacyjna z odzyskiem ciepła jest produkowana przez Systemair.