

Klimakonwektory		Jednofazowe								
		0.8 kW	0.9 kW	1.5 kW	1.8 kW	2.2 kW	3.3 kW	4.3 kW	4.6 kW	9.6 kW
Type		Compact units	Compact units	Compact units	Compact units	Compact units	Compact units	Compact units	Compact units	High Static Pressure
Left side connection		PAW-FC-D11-1	PAW-FC-D15-1	PAW-FC-D24-1	PAW-FC-D28-1	PAW-FC-D40-1	PAW-FC-D55-1	PAW-FC-D65-1	PAW-FC-D90-1	PAW-FC-H150
Right side connection		PAW-FC-D11-1-R	PAW-FC-D15-1-R	PAW-FC-D24-1-R	PAW-FC-D28-1-R	PAW-FC-D40-1-R	PAW-FC-D55-1-R	PAW-FC-D65-1-R	PAW-FC-D90-1-R	PAW-FC-H150-R
Total cooling capacity (Med) (1)	kW	1,0	1,2	2,0	2,4	3,2	4,6	6,1	6,1	11,9
Total cooling capacity (S-Hi) (1)	kW	1,5	1,7	2,5	3,2	4,6	5,8	7,3	8,1	14,8
Sensible cooling capacity (Med) (1)	kW	0,8	0,9	1,5	1,8	2,2	3,3	4,3	4,6	9,6
Sensible cooling capacity (S-Hi) (1)	kW	1,1	1,3	1,9	2,3	3,3	4,5	5,1	6,3	12,9
Heating capacity (Med) (1)	kW	1,4	1,5	2,4	2,9	4,1	5,3	7,9	8,1	14,9
Heating capacity (S-Hi) (1)	kW	2,0	2,2	3,1	4,0	5,7	7,1	9,3	11,6	19,9
Power consumption (S-Lo)	W	13	10	16	15	28	37	53	90	180
Power consumption (Med)	W	24	18	37	37	55	75	100	112	421
Power consumption (S-Hi)	W	36	29	45	56	72	105	147	188	675
Fuse rating	A	2	2	2	2	2	2	2	2	6
Dimension (Height) (2)	mm	220	220	220	220	220	220	220	220	376
Dimension (Width) (2)	mm	570	570	753	938	1122	1307	1121	1316	1600
Dimension (Depth) (2)	mm	430	430	430	430	430	430	530	530	798
Weight (3)	kg	13	13	15	20	22	26	27	38	63
Sound power global (S-Lo)	dB(A)	33	31	30	30	34	38	43	50	52
Sound power global (Med)	dB(A)	40	43	45	44	46	51	56	55	64
Sound power global (S-Hi)	dB(A)	49	50	52	51	56	58	61	64	71
Sound pressure global (S-Lo)	dB(A)	24	22	21	21	25	29	34	41	31
Sound pressure global (Med)	dB(A)	31	34	36	35	37	42	47	46	45
Sound pressure global (S-Hi)	dB(A)	40	41	43	42	47	49	52	55	51
Static pressure (Max)	Pa	30	30	50	50	70	70	70	70	110
Air flow (Med) (1)	m³/h	190	179	274	357	486	640	893	936	2112
Air flow (S-Hi) (1)	m³/h	283	265	390	499	716	933	1064	1397	3176
Water pressure drop (Med)	kPa	19,5	3,9	19,3	17,1	22,8	37,4	15,4	19,3	19,8
Water pressure drop (S-Hi)	kPa	39,2	6,3	28,8	28,0	46,9	60,2	21,5	32,5	26,1
Fan speeds		3 speeds	3 speeds	3 speeds	3 speeds	3 speeds	3 speeds	3 speeds	3 speeds	3 speeds
Fan motor and number of speeds		AC 5 speeds	AC 5 speeds	AC 5 speeds	AC 5 speeds	AC 5 speeds	AC 5 speeds	AC 5 speeds	AC 5 speeds	AC 5 speeds
Drain pan and air filter		Included	Included	Included	Included	Included	Included	Included	Included	Included
Water connections	Inch	1/2	1/2	1/2	1/2	1/2	1/2	3/4	3/4	1

(1) Przepływ powietrza i wydajność przy ciśnieniu statycznym równym 0 Pa.

(2) Z mis odpyw i skrzynek elektrycznych.

(3) Bez wody.

* Wydajność wyznaczona w warunkach: Chłodzenie: powietrze: 27°C ts / 19°C tm, woda lodowa: 7°C / 12°C – Ogrzewanie: powietrze: 20°C ts, woda gorąca: 50°C / 45°C.

** Klimakonwektory są produkowane przez Systemair.